WBS Elements: 11CR.20061.11, 11M.200615.11, 11CR.20141.11, 11M.201415.11, 11CR.20861.11, PROJ. REFERENCE NO. SHEET NO. See to the Left TCP-3 11M.208615.11, 11CR.20971.11 TWO-WAY UNDIVIDED ** (L-LINES) HIGHWAY WORK ZONE NORTH CAROLINA TRANSPORTATION HIGHWAYS RECOMMENDED WORK MINIMUM SIGN SPACING W20-1 48"X48" ROAD WORK G20-2a 48"x24" ပ POSTED SPEED LIMIT (8) (M.P.H.) ≤ 50 500' RALEIGH, OF. ≥ 55 1000' DIVISION P 9F -CONSTRUCTION LIMITS-STATE **END** DEPT. WORK G20-2a 48"X24" ROAD WORK ROADWAYS INTERSECTING ALONG 2 WAY UNDIVIDED WORK ZONE (Y-LINES) -Y- LINES MAIN ROADWAY WORK ZONE GNS IDED WORK CONSTRUCTION G20-2a 48"X24" LIMITS

CONSTRUCTION

-Y- LINE

G20-2a 48"X24"

AHEAD


WORK

GENERAL NOTES

- USE FLUORESCENT ORANGE SHEETING (TYPE VII OR HIGHER) ON ALL ADVANCED WORK ZONE SIGNS.
- DO NOT INSTALL ADVANCE WARNING SIGNS MORE THAN 3 DAYS PRIOR TO BEGINNING OF WORK.
- ALL SIGN SPACING DIMENSIONS ARE APPROXIMATE, FIELD ADJUST AS NECESSARY OR AS DIRECTED.
- USE PORTABLE WORK ZONE SIGNS ONLY WITH PORTABLE WORK ZONE SIGN STANDS SPECIFICALLY DESIGNED FOR ONE ANOTHER. PORTABLE WORK ZONE SIGNS MAY BE ROLL UP OR APPROVED COMPOSITE.
- PROVIDE PORTABLE WORK ZONE SIGN STANDS, PORTABLE SIGNS AND SIGN SHEETING WHICH ARE LISTED ON THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION'S APPROVED PRODUCT LIST OR ACCEPTED AS TRAFFIC QUALIFIED BY THE TRAFFIC CONTROL UNIT.
- ** TWO-WAY UNDIVIDED ADVANCE WARNING SIGN CONFIGURATION MAY BE USED ON URBAN MULTI-LANE FACILITIES WHERE CONDITIONS LIMIT THE USE OF DUAL MOUNTED SIGNS AS DETERMINED BY THE ENGINEER.

LEGEND PORTABLE SIGN DIRECTION OF TRAFFIC FLOW

SHEET 1 OF 1



 		-	•••	
	, OHOLHER	20	,	
3		198		
•	4	Ş)¢:	
		, , , , , , , , , , , , , , , , , , ,	*	
	CONT	100		

DWG. BY:

DETAIL DRAWING

FOR ADVANCED	TWO-WAY UNDIVID WORK ZONE WARNI	ED NG SIGN	IS	
NONE	OMCINETE !	REVISIONS		
		7-98	10/01	
4		10-98	03/04	
BY:		01/01 11/0		
D BY:	C CONTROL	CADD FILE		

S

Ž

WARN.

ON

WORK

UNDIV

OMT M

FOR

DRAWING

DETAIL